

Netfonic

DESCRIPCIÓN DE PRODUCTOS

- **Servicio Telefónico NETFONIC**



- Equipo: Linksys PAP2(T), Linksys RT31P2 e IP PHONE ACT P160S
- Servicio sin necesidad de computadora personal
- Conéctalo al cable/dsl modem o a un router.
- Requiere de servicio de Internet de banda ancha (mínimo 256)
- **Servicios incluidos en el plan:**
 - Llamadas limitadas o ilimitadas de acuerdo al plan
 - Recepción de llamadas ilimitadas
 - Buzón de voz
 - Identificación de llamadas
 - Llamada en espera
 - Sígueme/Ruteo de llamada (Solo en Estados Unidos)
 - Conferencia tripartita
 - Transferencia de llamadas
 - Bloqueo de llamadas identificadas
 - Regreso de llamada automática
 - Call Hunt (ruteo de llamadas a otra línea Netfonic en caso de estar ocupado)
 - Ring List (El teléfono 800 o virtual podrá sonar en múltiples líneas)
 - Portabilidad
 - VPN
 - Selección de código de área en Estados Unidos
 - Bloqueo de llamadas internacionales
- **Servicios adicionales con costo:**
 - Número 800 disponible
 - Número virtual adicional disponible
 - Llamadas internacionales a bajas tarifas
 - Cambio de número telefónico
 - Cambio de plan

- **Servicio IPPBX NETFONIC**



- SIP Application Server, Proxy, Registrar and Location Server (RFC3261)
- Multiple Service Provider Lines / SIP Account Support (4)
- Shared Line Appearance (SLA)
- Automated Attendant (AA)
- Configurable AA Answer Delay
- Interactive Voice Response (IVR)
- Recordable IVR Prompts
- Automatic Call Distribution (ACD)
- Configurable Call Routing
 - Least Cost Routing
 - Multiple DID Numbers Per VoIP Line
 - Call Routing to Multiple Extensions or Targeted User
 - Call Hunting
 - Sequential, Round Robin, Random
- Phone Configuration and Management Server
 - Discovery and Configuration of IP Phones
 - Assignment of Extension - Assignment of Dial plan
 - Proxy Logging of SIP Messages
 - Phone Firmware Upgrade Management
- Corporate Directory with Automatic Update
- Configuration and Maintenance via Web Interface (Local or Remote)
 - Status Display of All Connections
 - Remote Configuration via
 - HTTPS with XML Formatted Files
 - HTTP or TFTP with 256-Bit Encrypted Binary Files
- Call Park
 - User Definable Parking Space Number
- Call Unpark
- Call Transfer
- Call Forward
- Group Paging
- Intercom
- Directed Call Pick Up
- Group Call Pick Up
- Music / Information via Streaming Audio Server (SAS) for Calls:
 - On Hold
 - Parked in the Parking Lot
 - Being Transferred
- Simultaneous Ringing (Find Me Service)
- Do Not Disturb
- Voice Mail Integration
 - Service Provider Based
 - Voice Mail Notification via SUBSCRIBE / NOTIFY
 - Forward Call Directly to Voice mail
- Integrated Media Proxy or Direct RTP Routing to ITSP
- Differentiated Services (DiffServ) / Type of Service (TOS) Support
- Two FXS Ports for Phones, Fax machines, Media Adapters
- Voice encoding according to G.711 (64kbit/s)
- Fax Support using G.711 Pass-Through or T.38
- Echo Cancellation (G.165)

Additional Features when used with SPA IP Phones

- Line Status - Active Line Indication, Name/Number
 - Digits Dialed with Number Auto-Completion
 - Call Hold
 - Call Waiting
 - Call Transfer - Attended and Blind
 - Call Conferencing
 - Automatic Redial
 - Call Pick Up - Selective and Group **
 - Call Swap
 - Call Forwarding - Unconditional, No Answer, On Busy
 - Hot Line and Warm Line Automatic Calling
 - Call Log (60 entries each): Made, Answered, Missed Calls
 - Personal Directory with Auto-dial (100 entries)
 - Do Not Disturb
 - URI (IP) Dialing Support (Vanity Numbers)
 - On Hook Default Audio Configuration (Hands Free/Headset)
 - Multiple Ring Tones with Selectable Default Ring Tone per Line
 - Called Number with Directory Name Matching
 - Calling Number with Name - Directory Matching or via Caller ID
 - Subsequent Incoming Calls with Calling Name and Number
 - Date and Time with Intelligent Daylight Savings Support
 - Call Duration with Call Time Stamp Stored in Call Logs
 - Name/Identity (Text) Display at Start Up
 - Distinctive Ringing Based on Calling and Called Number
 - User Downloadable Ring Tones and Ring Tone Generator (Free from www.linksys.com)
 - Download on Demand Ring Tones – 10
 - Speed Dial Support • Configurable Dial/Numbering Plan Support - per Line
 - DNS SRV and Multiple A Records for Proxy Lookup and Proxy Redundancy
 - Syslog, Debug, Report Generation and Event Logging
 - Secure Call Encrypted Voice Communication Support
 - Built-in Web Server for Admin and Config with Multiple Security Levels
 - Automated Provisioning, Multiple Schemes-Up to 256 Bit Encryption: (HTTP, HTTPS, TFTP)
 - Require Admin Password to Reset Unit to factory Defaults Option
- ** Service feature availability is call feature server platform dependent.
SPA9000 upgrade license to support 16 IP Phones: SPA9000UPG.

Security

- Password Protected System Reset to Factory Default
- Password Protected Admin and User Access Authority
- HTTPS with Factory Installed Client Certificate
- HTTP Digest - Encrypted Authentication via MD5 (RFC 1321)
- Up to 256-bit AES Encryption